

μWeb - Bug #811

HEAD request returns the whole page (like a GET request) and not only headers.

2012-05-10 10:22 - Niek Bergman

| | | | |
|---|--------------------|------------------------|------------|
| Status: | Closed | Start date: | 2012-05-10 |
| Priority: | Normal | Due date: | |
| Assignee: | Niek Bergman | % Done: | 100% |
| Category: | | Estimated time: | 1.00 hour |
| Target version: | μWeb alpha release | Spent time: | 1.00 hour |
| Description | | | |
| Doing a HEAD request on a μWeb served page gives back a full page (as if the request were a GET request), and not only the headers of that page. RFC2616 specifies "The HEAD method is identical to GET except that the server MUST NOT return a message-body in the response" | | | |

Associated revisions

Revision 222:5ca12ee8c3c0 - 2012-05-10 18:53 - Elmer de Looff

Reduced Apache mock code and simplified return from uweb.Handler. Fixed request module to only actually send data for requests other than HEAD. This resolves #811.

History

#1 - 2012-05-10 10:27 - Elmer de Looff

- Assignee set to Elmer de Looff
- Target version set to μWeb alpha release
- Estimated time set to 1.00 h

Needs fixing before public release.

#2 - 2012-05-10 18:56 - Elmer de Looff

- Status changed from New to Resolved
- % Done changed from 0 to 70

Applied in changeset [5ca12ee8c3c0](#).

#3 - 2012-05-10 18:56 - Elmer de Looff

- Assignee changed from Elmer de Looff to Niek Bergman

Niek,

Please confirm this works for you as well.

#4 - 2012-05-11 09:33 - Niek Bergman

Confirmed to be working with latest μWeb -- only headers get returned currently like they should.

#5 - 2012-05-11 09:39 - Elmer de Looff

- Status changed from Resolved to Closed
- % Done changed from 70 to 100