

μWeb - Feature #873

Add localpath var to router.py to allow it to run from a subdirectory instead of the virtualhost root

2012-06-15 11:46 - Rudi Daemen

| | | | |
|--|----------|------------------------|------------|
| Status: | Resolved | Start date: | 2012-06-15 |
| Priority: | Low | Due date: | |
| Assignee: | | % Done: | 70% |
| Category: | | Estimated time: | 0.00 hour |
| Target version: | | Spent time: | 0.00 hour |
| Description | | | |
| Minor change, something like this: | | | |
| <pre>LOCALPATH = '/uweb' ROUTES = ((LOCALPATH + '/', 'Index'), (LOCALPATH + '/test', 'Test'), (LOCALPATH + '/(.*)', 'FourOhFour'))</pre> | | | |
| This might simplify installations/configuration of pages which require no customization of available routes. | | | |

Associated revisions

Revision 338:65f06296877f - 2013-07-14 16:18 - Elmer de Looff

Added a proper default prefix for the routes. This resolves #873.

History

#1 - 2013-07-14 16:12 - Elmer de Looff

This is resolved in [r337](#)

There is now a configurable route prefix. In the router file, defining ROUTE_PREFIX sets this common prefix for all routes. This prefix is placed in front of all routes verbatim, any slashes required to separate paths must be added manually.

#2 - 2013-09-13 13:53 - Elmer de Looff

- Status changed from New to Resolved

- % Done changed from 0 to 70

Applied in changeset uweb|commit:65f06296877f.